



**APPLICATIONS**

The Vansan VSS pumps are designed for borehole installations as well as lifting, distribution and pressurization applications.

**CONSTRUCTION FEATURES**

Diffusers, Impellers, Brackets, Suction case and Discharge case completely made of stainless steel AISI 304 in order to provide maximum strength, durability, wear and tear resistance.

**Max. Permissible Sand/silt:** 50g/m<sup>3</sup>

**Max. Ambient Temperature:** 30°C

**Installation:** Vertical/Horizontal.

**TECHNICAL DATA**

Model	Motor Type	Electrical Data			L2 [mm]	L [mm]	L1 [mm]	D [mm]	D1 [mm]	Outlet	Weight [kg]
		P2 Nominal		In A							
		[kW]	[HP]								
VSS60-4	6GF	7.5	10	17.2	1490	660	830	141	132	4"	63.2
VSS60-6	6GF	11	15	23.7	1784	730	1054				76
VSS60-8	6GF	15	25	33.1	2250	860	1390				98
VSS60-10	6GF	18.5	30	41.8	2534	920	1614				106.6
VSS60-12	6GF	22	40	46.2	3000	1050	1950				130.8
VSS60-14	6GF	26.5	40	55.1	3224	1050	2174				135.8
VSS60-17	6GF	30	50	61.7	3690	1180	2510				155.8

