

MICRO FILTERS 85" STAINLESS STEEL



MODEL	DIA (mm)	HEIGHT (mm)	No. OF CARTRIDGES	MAX. PRESSURE (BAR)	INLET SIZE (Inch)	OUTLET SIZE (Inch)
3 x 10"	170	450	3	6	25	25
5 x 10"	200	450	5	6	40	40
7 x 10"	250	450	7	6	40	40
3 x 20"	170	700	3	6	25	25
5 x 20"	200	700	5	6	40	40
7 x 20"	230	700	7	6	50	50

MICRO FILTERS UPVC



MODEL	DIA (mm)	HEIGHT (mm)	No. OF CARTRIDGES	MAX. PRESSURE (BAR)	INLET SIZE (Inch)	OUTLET SIZE (Inch)
HPCF-5DC1 10"	257	475	5	6	2	2
HPCF-5DC2 20"	257	725	5	6	2	2

YARN CARTRIDGES



TYPE	MODEL	FLOW RATE (m ³ /hr)	DIA (mm)	HEIGHT	MICRON OPTIONS	MAX. TEMP °C
TAW 10" PP YARN CARTIDGE	PS10	1.1	63	250	0.5, 1,5,10	50
TAW 10" JUMBO PP YARN CARTIDGE	PS10B	1.8	110	250	0.5, 1,5,10	50
TAW 20" PP YARN CARTIDGE	PS20	2.2	63	510	0.5, 1,5,10	50
TAW 20" JUMBO PL YARN CARTIDGE	PS20B	3	110	510	0.5, 1,5,10	50

PLEATED CARTRIDGES



TYPE	MODEL	FLOW RATE (m ³ /hr)	DIA (mm)	HEIGHT	MICRON OPTIONS	MAX. TEMP °C
TAW 10" PL PLEATED CARTIDGE	PL10	1.1	70	250	1,5,10	60
TAW 10" JUMBO PL PLEATED CARTIDGE	PL10B01	1.8	110	250	1,5,10	60
TAW 20" PL PLEATED CARTIDGE	PL20	2.2	70	510	1,5,10	60
TAW 20" JUMBO PL PLEATED CARTIDGE	PL20B	3	110	510	1,5,10	60

GRANULAR ACTIVATED CARBON CARTRIDGES



TYPE	MODEL	FLOW RATE (m ³ /hr)	DIA (mm)	HEIGHT	MICRON OPTIONS	MAX. TEMP °C
TAW 10" GRANULAR ACTIVATED CARBON CARTIDGE	GAC-10	0.25	73	250	-	52
TAW 10" JUMBO GRANULAR ACTIVATED CARBON CARTIDGE	GAC-10B	0.5	110	250	-	52
TAW 20" GRANULAR ACTIVATED CARBON CARTIDGE	GAC-20	0.5	73	510	-	52
TAW 20" JUMBO GRANULAR ACTIVATED CARBON CARTIDGE	GAC-20B	1	110	510	-	52

BLOCK CARBON CARTRIDGES



TYPE	MODEL	FLOW RATE (m ³ /hr)	DIA (mm)	HEIGHT	MICRON OPTIONS	MAX. TEMP °C
TAW 10" BLOCK CARBON CARTIDGE	CTO-10	0.25	70	250	-	52
TAW 10" JUMBO BLOCK CARBON CARTIDGE	CTO-10B	0.5	110	250	-	52
TAW 20" BLOCK CARBON CARTIDGE	CTO-20	0.5	70	510	-	52
TAW 20" JUMBO BLOCK CARBON CARTIDGE	CTO-20B	1	110	510	-	52