## TAFLO

### WP SERIES PETROL ENGINE PUMPS






WP20/30/40 WP20H-2


**Performance Curve** 30 10 **WP20 WP30** WP40 36 42 48

# 40 NP20H 10 10 40 FLOW(m3/h)

## **APPLICATION**

TAFLO WP range of Engine pumps are superior quality self priming petrol engine driven pumps designed for water transfer, irrigation and fire fighting. They are fitted with a frame which makes them sturdy and robust and the engines are designed for long hours of operation. Pump housing and impeller are made of high quality Alluminium for corrosion resistance





#### **TECHNICAL DATA**

| i I I I I I I I I I I I I I I I I I I I |   |          |          |        |         |
|---|---|----------|----------|--------|---------|
| Model                                   |   | WP20     | WP30     | WP40   | WP20H-2 |
| Max Flow Rate (m3/h)                    |   | 30       | 60       | 90     | 35      |
| Head (m)                                |   | 25       | 28       | 25     | 60      |
| Suction (m)                             |   | 7        | 7        | 7      | 7       |
| Outlet size (inches)                    |   | 2        | 3        | 4      | 2       |
| Inlet size(inches)                      |   | 2        | 3        | 4      | 2       |
| Speed (rpm)                             |   | 3600     | 3600     | 3600   | 3600    |
| Engine model                            |   | NL168F-1 | NL168F_1 | NL188F | NL170F  |
| Maximum output power (HP)               |   | 6.5      | 6.5      | 13     | 7       |
| Fuel tank capacity (L)                  |   | 3.6      | 3.6      | 6.5    | 3.6     |
| Engine oil capacity (L)                 |   | 0.6      | 0.6      | 1.1    | 0.6     |
| Dimensions(mm)                          | L | 475      | 520      | 590    | 505     |
|   | W | 475      | 385      | 450    | 380     |
|   | Н | 375      | 422      | 530    | 445     |
| Net Weight(kg)                          |   | 23       | 25       | 64     | 24      |